

**Genetron® 23**

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Genetron® 23  
MSDS Number : 000000011258  
Product Use Description : Refrigerant

Company : Honeywell International, Inc.  
101 Columbia Road  
Morristown, NJ 07962-1057

For more information call : 800-522-8001  
(Monday-Friday, 9:00am-5:00pm)

**In case of emergency call : Medical: 1-800-498-5701 or +1-651-523-0309**  
: **Transportation: 1-800-424-9300 or +1-703-527-3887**  
: (24 hours/day, 7 days/week)

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : slight sweet ether-like

Hazard Summary : Warning! Container under pressure. This product is not flammable at ambient temperatures and atmospheric pressure. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. May cause drowsiness and dizziness. Do not breathe vapour. Irritating to eyes and skin. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250 C), decomposition products may include hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

**Potential Health Effects**

Skin : Avoid skin contact with leaking liquid (danger of frostbite).

**Genetron® 23**

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

- May cause frostbite.  
Irritating to skin.
- Eyes : Causes serious eye irritation.  
May cause frostbite.
- Ingestion : Unlikely route of exposure.  
Effects due to ingestion may include:  
Gastrointestinal discomfort
- Inhalation : Gas reduces oxygen available for breathing.  
Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating.  
Inhalation may cause central nervous system effects.  
May cause cardiac arrhythmia.  
Vapours may cause drowsiness and dizziness.
- Chronic Exposure : None known.

**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No.	Concentration
Trifluoromethane	75-46-7	99.50%

**SECTION 4. FIRST AID MEASURES**

- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids,

## Genetron® 23

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

### Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

## SECTION 5. FIRE-FIGHTING MEASURES

Flash point : not applicable

Ignition temperature : 765 °C (1,409 °F)

Lower explosion limit : None

Upper explosion limit : None

Suitable extinguishing media : The product is not flammable.  
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards during fire fighting : Contents under pressure.  
This product is not flammable at ambient temperatures and atmospheric pressure.  
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.  
Container may rupture on heating.  
Cool closed containers exposed to fire with water spray.  
Do not allow run-off from fire fighting to enter drains or water courses.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
Rapid evaporation of the liquid may cause frostbite.  
In case of fire hazardous decomposition products may be produced such as:

**Genetron® 23**

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

Hydrogen fluoride  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Carbonyl halides

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit. No unprotected exposed skin areas.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions : Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Wear personal protective equipment. Unprotected persons must be kept away. Remove all sources of ignition. Avoid skin contact with leaking liquid (danger of frostbite). Ventilate the area. After release, disperses into the air. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Avoid accumulation of vapours in low areas. Unprotected personnel should not return until air has been tested and determined safe. Ensure that the oxygen content is  $\geq 19.5\%$ .

Environmental precautions : Prevent further leakage or spillage if safe to do so. The product evaporates readily.

Methods for cleaning up : Ventilate the area.

**SECTION 7. HANDLING AND STORAGE****Handling**

Handling : Handle with care. Avoid inhalation of vapour or mist. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Use only in well-ventilated areas. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Follow all standard safety precautions for handling and use of compressed gas cylinders. Use authorized cylinders only. Protect cylinders from physical damage.

## Genetron® 23

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

Do not puncture or drop cylinders, expose them to open flame or excessive heat.  
 Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.  
 Do not remove screw cap until immediately ready for use. Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.  
 Can form a combustible mixture with air at pressures above atmospheric pressure.

### Storage

Requirements for storage areas and containers : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
 Keep containers tightly closed in a dry, cool and well-ventilated place.  
 Storage rooms must be properly ventilated.  
 Ensure adequate ventilation, especially in confined areas.  
 Protect cylinders from physical damage.  
 Store away from incompatible substances.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.  
 Avoid contact with skin, eyes and clothing.  
 Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.  
 Perform filling operations only at stations with exhaust ventilation facilities.

Eye protection : Wear as appropriate:  
 Safety glasses with side-shields  
 If splashes are likely to occur, wear:  
 Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves  
 In case of contact through splashing:  
 Protective gloves  
 Neoprene gloves  
 Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).

**Genetron® 23**

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

- Wear cold insulating gloves/face shield/eye protection.
- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.  
Wear a positive-pressure supplied-air respirator.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
Ensure adequate ventilation, especially in confined areas.  
Avoid contact with skin, eyes and clothing.  
Remove and wash contaminated clothing before re-use.  
Keep working clothes separately.

**Exposure Guidelines**

Contains no substances with occupational exposure limit values.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquefied gas
- Color : colourless
- Odor : slight sweet ether-like
- Molecular Weight : 70 g/mol
- pH : neutral
- Freezing point : -155 °C (-247 °F)
- Boiling point/boiling range : -82.1 °C (-115.8 °F)
- Vapor pressure : 42,982 hPa  
at 21.1 °C (70.0 °F)
- Relative vapour density : 2.4  
(Air = 1.0)
- Partition coefficient: n-octanol/water : no data available
- Solubility in other solvents : no data available

**Genetron® 23**

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

**SECTION 10. STABILITY AND REACTIVITY**

- Conditions to avoid : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.  
Decomposes under high temperature.  
Some risk may be expected of corrosive and toxic decomposition products.  
Can form a combustible mixture with air at pressures above atmospheric pressure.  
Do not mix with oxygen or air above atmospheric pressure.
- Materials to avoid : Finely divided aluminium  
Potassium  
Calcium  
Powdered metals  
Aluminium  
Magnesium  
Zinc
- Hazardous decomposition products : Halogenated compounds  
Hydrogen fluoride  
Carbonyl halides  
Carbon oxides
- Thermal decomposition : >250 °C  
To avoid thermal decomposition, do not overheat.
- Hazardous reactions : Hazardous polymerisation does not occur.  
Stable under normal conditions.

**SECTION 11. TOXICOLOGICAL INFORMATION**

- Acute inhalation toxicity : LC50: > 663000 ppm  
Species: rat
- Sensitisation : Cardiac sensitization  
Species: dogs  
Note: Threshold - >800,000 ppm

**Genetron® 23**

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

**SECTION 12. ECOLOGICAL INFORMATION****Further information on ecology**

Additional ecological information : Gas, insoluble in water.  
 This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.  
 This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere.  
 To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Waste Information: Observe all Federal, State, and Local Environmental regulations.  
 Additional advice : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

**SECTION 14. TRANSPORT INFORMATION**

**DOT** UN/ID No. : UN 1984  
 Proper shipping name : Trifluoromethane  
 Class : 2.2  
 Packing group  
 Hazard Labels : 2.2

**IATA** UN/ID No. : UN 1984  
 Description of the goods : Trifluoromethane  
 Class : 2.2  
 Hazard Labels : 2.2  
 Packing instruction (cargo aircraft) : 200  
 Packing instruction (passenger aircraft) : 200

**IMDG** UN/ID No. : UN 1984  
 Description of the goods : Trifluoromethane  
 Class : 2.2  
 Hazard Labels : 2.2  
 EmS Number : F-C



**Genetron® 23**

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

Marine pollutant : no

**SECTION 15. REGULATORY INFORMATION****Inventories**

- 1907/2006 (EU) : This mixture contains only ingredients which have been subject to a pre-registration according to Regulation (EC) No. 1907/2006 (REACH).
- US. Toxic Substances Control Act : On TSCA Inventory
- Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory
- Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) : All components of this product are on the Canadian DSL list.
- Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory
- Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory
- Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory
- China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory
- NZIOC - New Zealand : On the inventory, or in compliance with the inventory

**National regulatory information**

- SARA 311/312 Hazards** : Acute Health Hazard  
Sudden Release of Pressure Hazard

**Genetron® 23**

Version 2

Revision Date 10/04/2010

Print Date 11/15/2010

**California Prop. 65** : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**WHMIS Classification** : A  
 This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**Global warming potential** : 12,000

**SECTION 16. OTHER INFORMATION**

	<b>HMIS III</b>	<b>NFPA</b>
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0