

Version 2

Revision Date 10/25/2007

Print Date 10/25/2007

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genetron MP39 (R-401A)
MSDS Number : 000000011265
Product Use Description : Refrigerant

Company : Honeywell International, Inc.
101 Columbia Road
Morristown, NJ 07962-1057

For more information call : 800-522-8001
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701
: **Transportation: 1-800-424-9300 or 703-527-3887**
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : Liquefied gas

Color : colourless

Odor : slight sweet ether-like

Hazard Summary : Warning! Container under pressure. This product is not flammable at ambient temperatures and atmospheric pressure. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. May cause drowsiness and dizziness. Do not breathe vapour. Irritating to eyes and skin. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250°C), decomposition products may include hydrochloric acid (HCl), hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

Potential Health Effects

Skin : Avoid skin contact with leaking liquid (danger of frostbite).
May cause frostbite.
Irritating to skin.

Eyes : Causes severe eye irritation.
May cause frostbite.

Ingestion : Unlikely route of exposure.

Version 2

Revision Date 10/25/2007

Print Date 10/25/2007

Effects due to ingestion may include:
Gastrointestinal discomfort

Inhalation : Gas reduces oxygen available for breathing.
Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating.
Inhalation may cause central nervous system effects.
May cause cardiac arrhythmia.
Vapours may cause drowsiness and dizziness.

Chronic Exposure : None known.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight %
Chlorodifluoromethane	75-45-6	52.50 - 54.50
1-Chloro-1,2,2,2-tetrafluoroethane	2837-89-0	33.00 - 34.00
1,1-Difluoroethane	75-37-6	11.50 - 13.50
1-Chloro-1,1,2,2-tetrafluoroethane	354-25-6	<=1.70

SECTION 4. FIRST AID MEASURES

Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.

Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with

Version 2

Revision Date 10/25/2007

Print Date 10/25/2007

special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIRE-FIGHTING MEASURES

- Flash point : not applicable
- Lower explosion limit : None
- Upper explosion limit : None
- Suitable extinguishing media : The product is not flammable. ASHRAE 34
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during fire fighting : Contents under pressure.
This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
In case of fire hazardous decomposition products may be produced such as:
Gaseous hydrogen chloride (HCl).
Hydrogen fluoride
Carbon monoxide
Carbon dioxide (CO₂)
Carbonyl halides
- Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).

Version 2

Revision Date 10/25/2007

Print Date 10/25/2007

Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is $\geq 19.5\%$.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.

Methods for cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Handle with care.
Avoid inhalation of vapour or mist.
Do not get in eyes, on skin, or on clothing.
Wear personal protective equipment.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, expose them to open flame or excessive heat.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.
Can form a combustible mixture with air at pressures above atmospheric pressure.

Storage

Requirements for storage areas and containers : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Storage rooms must be properly ventilated.
Ensure adequate ventilation, especially in confined areas.
Protect cylinders from physical damage.
Store away from incompatible substances.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Protective measures : Do not breathe vapour.
 Avoid contact with skin, eyes and clothing.
 Ensure that eyewash stations and safety showers are close to the workstation location.

- Engineering measures : General room ventilation is adequate for storage and handling.
 Perform filling operations only at stations with exhaust ventilation facilities.

- Eye protection : Wear as appropriate:
 Safety glasses with side-shields
 If splashes are likely to occur, wear:
 Goggles or face shield, giving complete protection to eyes

- Hand protection : Leather gloves
 In case of contact through splashing:
 Protective gloves
 Neoprene gloves
 Polyvinyl alcohol or nitrile- butyl-rubber gloves

- Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
 Wear cold insulating gloves/face shield/eye protection.

- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.
 Wear a positive-pressure supplied-air respirator.
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
 For rescue and maintenance work in storage tanks use self-contained breathing apparatus.

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
 Ensure adequate ventilation, especially in confined areas.
 Avoid contact with skin, eyes and clothing.
 Remove and wash contaminated clothing before re-use.
 Keep working clothes separately.

Exposure Guidelines

Chlorodifluoromethane	75-45-6	ACGIH	TWA	1,000 ppm	
		NIOSH	REL	1,000 ppm	3,500 mg/m3
		NIOSH	STEL	1,250 ppm	4,375 mg/m3
		US CA OEL	TWA PEL	1,000 ppm	3,500 mg/m3
		OSHA Z1A	TWA	1,000 ppm	3,500 mg/m3
1-Chloro-1,2,2,2-tetrafluoroethane	2837-89-0	WEEL	TWA	1,000 ppm	

Version 2

Revision Date 10/25/2007

Print Date 10/25/2007

1,1-Difluoroethane 75-37-6 WEEL TWA 1,000 ppm 2,700 mg/m3

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Liquefied gas

Color : colourless

Odor : slight sweet ether-like

pH : neutral

Freezing point : not determined

Boiling point/boiling range : -33 °C (-27 °F)

Vapor pressure : 7,018 hPa
at 21.1 °C (70.0 °F)

Vapor pressure : 16,430 hPa
at 54.4 °C (129.9 °F)

Relative vapour density : 3.5
(Air = 1.0)

Density : 1.188 g/cm3
at 25 °C (77 °F)

Water solubility : 2.4 g/l
at 25 °C (77 °F)
at 1,013 hPa

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Decomposes under high temperature.
Some risk may be expected of corrosive and toxic decomposition products.
Can form a combustible mixture with air at pressures above atmospheric pressure.
Do not mix with oxygen or air above atmospheric pressure.

Materials to avoid : Finely divided aluminium
Potassium
Calcium
Powdered metals
Aluminium
Magnesium
Zinc

Version 2

Revision Date 10/25/2007

Print Date 10/25/2007

- Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:
Gaseous hydrogen chloride (HCl).
Gaseous hydrogen fluoride (HF).
Carbonyl halides
Carbon monoxide
Carbon dioxide (CO₂)
- Thermal decomposition : >250 °C
- Hazardous reactions : Hazardous polymerisation does not occur.
Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

- Acute inhalation toxicity : LC50 rat
Dose: > 300000 ppm
Exposure time: 4 h
Test substance: Chlorodifluoromethane (HCFC-22)
- Acute inhalation toxicity : LC50 rat
Dose: 360000 ppm
Exposure time: 4 h
Test substance: 2-chloro-1,1,1,2- tetrafluoroethane.
(HCFC-124)
- Additional advice : Acute Health Hazard
Chlorodifluoromethane (HCFC-22): Cardiac sensitisation threshold (dog): 50000 ppm.
2-chloro-1,1,1,2- tetrafluoroethane. (HCFC-124): Cardiac sensitisation threshold (dog): 25000 ppm.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Irritating to eyes and skin.
Rapid evaporation of the liquid may cause frostbite.
Avoid skin contact with leaking liquid (danger of frostbite).
May cause cardiac arrhythmia.
Chronic Health Hazard
In vitro tests did not show mutagenic effects
In vivo tests did not show mutagenic effects

SECTION 12. ECOLOGICAL INFORMATION

- Additional ecological information : This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.
This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.
Section 611 requires the following label text on all shipments of

Version 2

Revision Date 10/25/2007

Print Date 10/25/2007

this product:
Warning: Contains Chlorotetrafluoroethane (HCFC-124),
Warning: Contains Chlorodifluoromethane (HCFC-22),
a substance which harms public health and environment by
destroying ozone in the upper atmosphere.
Refer to sections 610 and 612 for list of acceptable and
unacceptable uses for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Information: Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of according to all federal, state and local applicable regulations.

Other Disposal Considerations: Observe all Federal, State, and Local Environmental regulations.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

SECTION 14. TRANSPORT INFORMATION

DOT Proper shipping name : LIQUEFIED GAS, N.O.S.
 UN-Number : 3163
 Class : 2.2
 Packing group :

IATA UN Number : 3163
 Description of the goods : LIQUEFIED GAS, N.O.S.
 Class : 2.2
 Hazard Label : 2.2
 Packing instruction (cargo : 200
 aircraft)
 Packing instruction : 200
 (passenger aircraft)

IMDG Substance No. : UN 3163
 Description of the goods : LIQUEFIED GAS, N.O.S.
 Class : 2.2
 Hazard Label : 2.2
 EmS Number : F-C
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

Material Safety Data Sheet
Genetron MP39 (R-401A)

Honeywell

Version 2

Revision Date 10/25/2007

Print Date 10/25/2007

- EU. EINECS : On or in compliance with the inventory
- US. Toxic Substances Control Act : On TSCA Inventory
- Australia. Industrial Chemical (Notification and Assessment) Act : On or in compliance with the inventory
- Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) : This product contains the following components that are not on the Canadian DSL nor NDSL lists.
- Japan. Kashin-Hou Law List : 1-Chloro-1,2,2,2-tetrafluoroethane 2837-89-0
: Not in compliance with the inventory
- Korea. Toxic Chemical Control Law (TCCL) List : 1-Chloro-1,1,2,2-tetrafluoroethane 354-25-6
: On or in compliance with the inventory
- Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On or in compliance with the inventory
- China. Inventory of Existing Chemical Substances : On or in compliance with the inventory
- TSCA 12B : US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)
1-Chloro-1,1,2,2-tetrafluoroethane 354-25-6

National regulatory information

- SARA 313 Components** : Chlorodifluoromethane 75-45-6
: 1-Chloro-1,2,2,2-tetrafluoroethane 2837-89-0
: 1-Chloro-1,1,2,2-tetrafluoroethane 354-25-6

- SARA 311/312 Hazards** : Acute Health Hazard
Sudden Release of Pressure Hazard

- California Prop. 65** : This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

Material Safety Data Sheet
Genetron MP39 (R-401A)

Honeywell

Version 2

Revision Date 10/25/2007

Print Date 10/25/2007

Massachusetts RTK	: 1,1-Difluoroethane	75-37-6
	: Chlorodifluoromethane	75-45-6
New Jersey RTK	: Chlorodifluoromethane	75-45-6
	: 1-Chloro-1,2,2,2-tetrafluoroethane	2837-89-0
	: 1,1-Difluoroethane	75-37-6
	: 1-Chloro-1,1,2,2-tetrafluoroethane	354-25-6
Pennsylvania RTK	: Chlorodifluoromethane	75-45-6
	: 1-Chloro-1,2,2,2-tetrafluoroethane	2837-89-0
	: 1,1-Difluoroethane	75-37-6

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health Hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0