

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genetron® 407C
MSDS Number : 00000009894
Product Use Description : Refrigerant

Company : Honeywell International, Inc.
101 Columbia Road
Morristown, NJ 07962-1057

For more information call : 800-522-8001
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701
: **Transportation: 1-800-424-9300 or +1-703-527-3887**
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : slight

Hazard Summary : Warning! Container under pressure. This product is not flammable at ambient temperatures and atmospheric pressure. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. May cause drowsiness and dizziness. Do not breathe vapour. Irritating to eyes and skin. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250 C), decomposition products may include hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

Potential Health Effects

Skin : Avoid skin contact with leaking liquid (danger of frostbite).
May cause frostbite.
Irritating to skin.

Eyes : Causes serious eye irritation.

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

- May cause frostbite.
- Ingestion : Unlikely route of exposure.
Effects due to ingestion may include:
Gastrointestinal discomfort
- Inhalation : Gas reduces oxygen available for breathing.
Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating.
Inhalation may cause central nervous system effects.
May cause cardiac arrhythmia.
Vapours may cause drowsiness and dizziness.
- Chronic Exposure : None known.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight %
Norflurane	811-97-2	52.00
Pentafluoroethane	354-33-6	25.00
Difluoromethane	75-10-5	23.00

SECTION 4. FIRST AID MEASURES

- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIRE-FIGHTING MEASURES

Flash point : not applicable

Lower explosion limit : None

Upper explosion limit : None

Suitable extinguishing media : The product is not flammable. ASHRAE 34
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards during fire fighting : Contents under pressure.
This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
In case of fire hazardous decomposition products may be produced such as:
Hydrogen fluoride
Carbon monoxide
Carbon dioxide (CO₂)
Carbonyl halides

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is $\geq 19.5\%$.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.
- Methods for cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE**Handling**

- Handling : Handle with care.
Avoid inhalation of vapour or mist.
Do not get on skin or clothing.
Wear personal protective equipment.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, expose them to open flame or excessive heat.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.
- Advice on protection against fire and explosion : The product is not flammable.
Can form a combustible mixture with air at pressures above atmospheric pressure.

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

Storage

Requirements for storage areas and containers : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Storage rooms must be properly ventilated.
Ensure adequate ventilation, especially in confined areas.
Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.
Do not get in eyes, on skin, or on clothing.
Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.
Perform filling operations only at stations with exhaust ventilation facilities.

Eye protection : Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves
In case of contact through splashing:
Protective gloves
Neoprene gloves
Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
Wear cold insulating gloves/face shield/eye protection.

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.
Wear a positive-pressure supplied-air respirator.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Ensure adequate ventilation, especially in confined areas.
Do not get in eyes, on skin, or on clothing.
Remove and wash contaminated clothing before re-use.
Keep working clothes separately.

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

Exposure Guidelines

1,1,1,2-Tetrafluoroethane	811-97-2	WEEL	TWA	1,000 ppm	4,240 mg/m ³
		HONEYWELL	TWA		1,000 ppm
Pentafluoroethane	354-33-6	WEEL	TWA	1,000 ppm	4,900 mg/m ³
		TX ESL	ST ESL	5,000 ppm	24500 ug/m ³
		HONEYWELL	TWA		1,000 ppm
Difluoromethane	75-10-5	WEEL	TWA	1,000 ppm	2,200 mg/m ³
		TX ESL	ST ESL	5,000 ppm	10600 ug/m ³
		HONEYWELL	TWA		1,000 ppm
		TX ESL	AN ESL	500 ppm	1060 ug/m ³

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquefied gas
Color	: colourless
Odor	: slight
pH	: neutral
	: no data available
Boiling point/boiling range	: -43.9 °C (-47.0 °F)
Vapor pressure	: 10,769 hPa at 21.1 °C (70.0 °F)
Vapor pressure	: 24,593 hPa at 54.4 °C (129.9 °F)
Relative vapour density	: 3 (Air = 1.0)
Density	: 1.16 g/cm ³ at 21.1 °C (70.0 °F)

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

Water solubility : 1.5 g/l

Partition coefficient:
n-octanol/water : log Pow: 1.06

Partition coefficient:
n-octanol/water : log Pow: 1.48

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Decomposes under high temperature.
Some risk may be expected of corrosive and toxic decomposition products.
Can form a combustible mixture with air at pressures above atmospheric pressure.
Do not mix with oxygen or air above atmospheric pressure.

Materials to avoid : Finely divided aluminium
Potassium
Calcium
Powdered metals
Aluminium
Magnesium
Zinc

Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:
Gaseous hydrogen fluoride (HF).
Carbonyl halides
Carbon monoxide
Carbon dioxide (CO₂)

Thermal decomposition : >250 °C

Hazardous reactions : Hazardous polymerisation does not occur.
Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50
no data available

Acute dermal toxicity
(Component) : Component: 75-09-2 Dichloromethane
LD50 rat
Dose: > 2,000 mg/kg

Acute inhalation toxicity : LC50 rat

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

	Dose: > 500000 ppm Exposure time: 4 h Test substance: 1,1,1,2-tetrafluoroethane (HFC-134a)
Acute inhalation toxicity	: LC50 rat Dose: 520000 ppm Exposure time: 4 h Test substance: Difluoromethane (HFC-32)
Acute inhalation toxicity	: LC50 rat Dose: > 800000 ppm Exposure time: 4 h Test substance: Ethane, pentafluoro- (HFC-125)
Skin irritation (Component)	Component: 75-09-2 Dichloromethane rabbit Moderate skin irritation
Eye irritation (Component)	Component: 75-09-2 Dichloromethane rabbit Moderate eye irritation
Repeated dose toxicity	: rat NOEL: > 10000 ppm
Additional advice	: Acute Health Hazard Difluoromethane. (HFC-32): Cardiac sensitisation threshold (dog): 350000 ppm. Ethane, pentafluoro- (HFC-125): Cardiac sensitisation threshold (dog): 75000 ppm. 1,1,1,2-tetrafluoroethane (HFC-134a): Cardiac sensitisation threshold (dog): 80000 ppm. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Irritating to eyes and skin. Rapid evaporation of the liquid may cause frostbite. Avoid skin contact with leaking liquid (danger of frostbite). May cause cardiac arrhythmia.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity to fish	: LC50 Species: not specified no data available
Toxicity to daphnia and other aquatic invertebrates.	: LC50 Species: not specified no data available

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

Toxicity to bacteria : LC50
Species: not specified
no data available

Additional ecological information : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.
This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Information: Observe all Federal, State, and Local Environmental regulations.
Additional advice : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

DOT UN-Number : 3340
Proper shipping name : REFRIGERANT GAS R 407C
Class : 2.2
Packing group
Hazard Label : 2.2

IATA UN Number : 3340
Description of the goods : REFRIGERANT GAS R 407C
Class : 2.2
Hazard Label : 2.2
Packing instruction (cargo aircraft) : 200
Packing instruction (passenger aircraft) : 200

IMDG Substance No. : UN 3340
Description of the goods : REFRIGERANT GAS R 407C
Class : 2.2
Hazard Label : 2.2
EmS Number : F-C
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

Inventories

EU. EINECS	:	On the inventory, or in compliance with the inventory
US. Toxic Substances Control Act	:	On TSCA Inventory
Australia. AICS	:	On the inventory, or in compliance with the inventory
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	:	All components of this product are on the Canadian DSL list.
Japan. ENCS	:	On the inventory, or in compliance with the inventory
Korea. KECI	:	On the inventory, or in compliance with the inventory
Philippines. PICCS	:	On the inventory, or in compliance with the inventory
China. IECSC	:	On the inventory, or in compliance with the inventory
TSCA 12B	:	US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)
		1,1,1,2-Tetrafluoroethane 811-97-2

National regulatory information

SARA 311/312 Hazards	:	Acute Health Hazard Sudden Release of Pressure Hazard
California Prop. 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer. Dichloromethane 75-09-2

Genetron® 407C

Version 2

Revision Date 07/22/2008

Print Date 07/22/2008

: WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.
Chloromethane 74-87-3

Massachusetts RTK : Dichloromethane 75-09-2

New Jersey RTK : 1,1,1,2-Tetrafluoroethane 811-97-2
: Pentafluoroethane 354-33-6
: Difluoromethane 75-10-5

Pennsylvania RTK : 1,1,1,2-Tetrafluoroethane 811-97-2
: Pentafluoroethane 354-33-6
: Difluoromethane 75-10-5

WHMIS Classification : A

Global warming potential : 1,990

Ozone depletion potential (ODP) : 0

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health Hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0